



DISC VALVE - DVR



Description:

- DVR is made of steel sheet
- Adjustable disc.
- Powder coated to RAL 9010/9016 as standard finish.
- DVR is installed by a built-in rear frame.

		Nominal (n). mm.					Air Flow, M ³ /H									
S = Opening in mm	80	100	125	160	200	Qv (M ³ /H)	20	40	60	80	100	150	200	300		
	-9					ΔP_t (Pa)	90									
						NR	-									
	-6	-9				ΔP_t (Pa)	45	170								
						NR	-	20								
	-3	-6	-12			ΔP_t (Pa)	20	80	200	300						
						NR	-	12	25	28						
	0	-3			-20	ΔP_t (Pa)	-10	50	120	200						
						NR	-	-	17	26						
	6		-6			ΔP_t (Pa)		30	70	120	200					
						NR		-	12	20	28					
	9	6				ΔP_t (Pa)		20	40	80	130					
						NR		-	-	15	22					
			0		-15	ΔP_t (Pa)		15	30	60	80	200				
						NR		-	-	11	18	30				
		12	6			ΔP_t (Pa)		10	20	40	60	150				
						NR		-	-	-	13	27				
				0		ΔP_t (Pa)			15	25	40	90	170			
						NR			-	-	9	21	30			
			12	6		ΔP_t (Pa)				15	25	60	100	220		
					NR				-	-	15	25	31			
			12	0	ΔP_t (Pa)					15	30	60	150			
					NR					-	10	18	30			

Ordering Key:

D	V	R	-	I	6	0
DVR: DISC VALVE						
REAR BUILT-IN FRAME FOR FIXING STANDARD FOR DVR						
SIZE: 80, 100, 125, 160 OR 200						

