



BETA
i n d u s t r i a l

index

>> **ELECTRIC DUCT HEATER**

01 - 03





ELECTRIC DUCT HEATER - EDH

ELECTRIC DUCT HEATER

DESCRIPTION & OPTIONS


- Slip-in type electric heater made of galvanized steel of appropriate gauge.
- Configuration of the electric heater can be arranged as per customer requirements.
- Heating elements are available in Tubular and Finned Tubular types.
- Available in ON/OFF and MULTISTAGE electric controls.
- Primary over temperature protection is provided by auto reset thermal disc-type cutout.
- Air flow switch (requires min Pt total pressure of 0.07 inch WG at the face of the electric coil).

OPTIONS:


The following components can be provided upon request:

- Secondary over temperature protection with manual reset (push button) thermal disc-type cutout.
- 24V transformer & control fuse.
- Magnetic / safety contactors.
- Line and control terminal blocks.
- Up to 3 stages of heater control.
- Door-interlocking disconnect switch.
- Main power fuses.
- Electronic Flow Sensor can be provided.

MINIMUM AIR VELOCITY REQUIREMENTS:



HEATER'S ELEMENT PRESSURE DROP DATA:





ELECTRIC DUCT HEATER - EDH

ELECTRIC DUCT HEATER

HEATER CONTROL & POWER:

$$kW = CFM \times \Delta T^{\circ}F / 3160 = m^3/h \times \Delta T^{\circ}C / 2769$$

CONVENTIONAL STAGED CONTROL:

SIZE	STAGES	1 PHASE	3 PHASE
		220V	380V
100	1,2	3.5 kW	3.5 kW
150	1,2	6.0 kW	6.0 kW
200	1,2,3	11.0 kW	11.0 kW
250	1,2,3	11.5 kW	17.0 kW
300	1,2,3	11.5 kW	30.0 kW
350	1,2,3	11.5 kW	39.0 kW
400	1,2,3	11.5 kW	39.0 kW

Notes:

- 1- Low watt density elements (Max. 35W/in2)
- 2- Min. kW:
 - Single Phase = 0.5 kW
 - Three Phase = 1.5 kW
- 3- Min. based on air velocity of 200 FPM across the coil.

* The Max Allowable KW shown is based on UL / NEC standards.

** The minimum air flow requirement for terminals with electric coils is the greater of 70 CFM/KW or the minimum allowable flow rate that can be accurately controlled. This allows proper operation of the electric coil and results in increased coil life with a maximum air temperature rise of 45° F to prevent thermal stratification in the space.

*** Uniform flow through a coil results in optimum performance, and therefore, we recommend a minimum length of 48" of full size discharge duct after the air terminal.





ELECTRIC DUCT HEATER - EDH

ELECTRIC DUCT HEATER

HEATER'S STANDARD & OPTIONAL FEATURES:

ELEMENT TYPE:	<input type="checkbox"/> TUBULAR	<input type="checkbox"/> FINNED TUBULAR
ELEMENT CONSTRUCTION:	<input type="checkbox"/> INCOLOY 800 Nickel Alloy (standard)	<input type="checkbox"/> S.S. ELEMENT
POWER PHASE:	<input type="checkbox"/> SINGLE	<input type="checkbox"/> 3 PHASE
POWER VOLTAGE:	<input type="checkbox"/> 220V	<input type="checkbox"/> 380V
POWER FREQUENCY:	<input type="checkbox"/> 50Hz	
CONTROL:	ON/OFF	
DISC-TYPE AUTOMATIC RE-SET THERMAL CUT-OUT	STANDARD	
MANUAL RE-SET THERMAL CUT-OUT	STANDARD	
AIR FLOW SWITCH (minimum 0.07" WG)	STANDARD <input type="checkbox"/> fixed (PDN)	
MAGNETIC CONTACTORS	STANDARD	
TRANSFORMER	STANDARD	
DISCONNECT SWITCH	OPTIONAL: <input type="checkbox"/> Disconnect switch (door interlock) (DS) <input type="checkbox"/> Toggle switch (TS)	
TIME DELAY SWITCH	OPTIONAL: <input type="checkbox"/> Thermal relay (RT)	
POWER FUSES	OPTIONAL: <input type="checkbox"/> Line fuses (LF)	
CONTROL FUSES	OPTIONAL	
PILOT LIGHT	OPTIONAL: <input type="checkbox"/> Line Power (LP) <input type="checkbox"/> Stage ON (LS) <input type="checkbox"/> Heating ON (LH) <input type="checkbox"/> Overheat (LO) <input type="checkbox"/> No airflow (LN)	
VOLT FREE CONTACTS	OPTIONAL	
AUTOMATIC CIRCUIT BREAKER	OPTIONAL	

ORDERING KEY

Ordering Key:



E	D	H	W	X	H	<input type="checkbox"/> . <input type="checkbox"/> KW
ELECTRIC DUCT HEATER						
SIZE: W X H						
LOAD: <input type="checkbox"/> . <input type="checkbox"/> KW						

